

System Description

The M7/M7T is an ergonomically designed portable and ease-of-use machine for multi-specialty use like adults, pregnant women, pediatric patients and neonates. It is intended for use in abdominal, gynecology, obstetrics, peripheral vascular, small parts, urological, cardiac, anesthesia, emergency, ICU/CCU, pediatrics and neonates, transcranial (neonatal cephalic), first aid, interventional, MSK, athletic medical treatment and intraoperative exams.

Dimensions and Weight

- Width: 361mm (14.21 inch)
- Depth: 357mm (14.06 inch)
- Height: 75mm (2.95 inch)
- Weight: approx. 6.5kg (including batteries and 4D board, without power adapter)

Electrical Power

AC adapter input

- Voltage
 - > 100-240V~ (AC adapter)
 - > 220-240V~, 50/60Hz (configured with UMT-300)
- Frequency: 50/60Hz
- Input power
 - > 1.5- 0.6A (AC adapter)
 - > 600 VA (configured with UMT-300)

AC adapter output:

- Voltage: 12V ===
- Output current: 10A

Battery

- Lithium-Ion Battery Pack: 11.1V === , 4500mAh

Operating Environment

Ambient temperature: 0°C ~ 40°C
Relative humidity: 30% ~ 85% (no condensation)
Atmospheric pressure: 700 hPa ~ 1060 hPa

Storage & Transportation Environment

Ambient temperature: -20°C ~ 55°C
Relative humidity: 30% ~ 95% (no condensation)
Atmospheric pressure: 700 hPa ~ 1060 hPa

Probe

Probe Types

- Linear array probe
- Phased array probe
- Convex array probe
- 4D mechanical volume probe

Scanning Methods

- Electronic convex with extend FOV
- Electronic linear with slant scanning and trapezoid
- Electronic sector

Probe Model

- C5-2s-----Convex Transducer
- V10-4s-----Cavity Micro-Convex Transducer
- V10-4Bs-----Cavity Micro-Convex Transducer
- 6C2s-----Micro-Convex Transducer
- 4CD4s-----4D Mechanical Volume Transducer
- 7L4As-----Linear Transducer
- L12-4s-----Linear Transducer
- L14-6s-----Linear Transducer
- L7-3s-----Linear Transducer
- 7L5s-----Linear Transducer
- P7-3s--High Frequency Phased Array Transducer
- P12-4s--High Frequency Phased Array Transducer
- P4-2s-----Phased Array Transducer
- L14-6Ns-----Linear Transducer
- CW2s-----Continuous Wave Transducer
- Available Needle-guided Bracket for Probe:
 - > C5-2s: NGB-006

- V10-4s/V10-4Bs: NGB-004
- 6C2s: NGB-005
- 7L4s: NGB-007
- L12-4s: NGB-007
- L14-6s: NGB-016
- L7-3s: NGB-007
- 7L5s: NGB-007
- P4-2s: NGB-011

- ✓ 1 Serial port
- ✓ 1 Audio output port: Left/Right
- ✓ 1 Mic In port
- ✓ 1 Remote control port
- ✓ 1 Composite video output port
- ✓ 1 DVI-I (Digital Video Interface-Integrated) output port
- V/A extend module
 - ✓ Audio input port Left/Right
 - ✓ Composite video input port
 - ✓ Separate video input port
- ECG module
 - ✓ ECG Lead port
 - ✓ Connection port: to connect to I/O extend module
 - ✓ Should be configured with I/O extend module

Appearance Design

- Display
 - 15inch LCD, High-Resolution 1024 X 768
 - Brightness Adjustment
 - Screen Saver: Time and graph presettable
 - Boot time: 50s
 - Boot time (from standby): 12s
 - Open angle adjustable: 150°
- Control Panel
 - Power/Battery Indicator
 - Alphanumeric Keys
 - Function Keys
 - Knobs
 - Ergonomic soft key operation
 - Backlight Keys
 - 8 segment TGC
 - Blank Keys for User-defined Functions
 - Trackball: color and Sensitivity Adjustment
 - Brightness adjustment
 - Integrated Speakers, Audio Volume Adjustment
- Handle
- Transducer port
 - 1 port, connect to a probe or the probe extend module
- Transducer locking lever
- Power input port
 - Connect to the power adapter
- I/O(input/output) extend port
 - connect to the I/O extend module
 - I/O extend module:
 - ✓ 2 USB port
 - ✓ 1 ECG port

- USB port: 2
- Ethernet port
 - Connect to the network
- S-Video separate video output
 - For image signal output
- Wireless LAN support
- Mobile Trolley
 - UMT-200
 - UMT-300
 - ✓ 15-inch Extra LCD Display (optional)
 - ✓ Power supply module (optional)
 - ✓ External DVD R/W Storage(optional)

Peripherals Supported

- Black / white video printer (Digital)
 - SONY UP-D897
 - MITSUBISHI P95DW-N
 - MITSUBISHI P93DC
- Color video printer(Digital): SONY UP-D23MD
- Graph / text printer
 - HP Deskjet D2568
 - HP OfficeJet J3600 (HP Officejet J3608 All-in-One)
 - HP Color LaserJet CM1015

Hardware Options

- External USB DVD-RW: SE-S224Q

- I/O extend module: IOM-21
- Probe extend module: PEM-21
- V/A extend module: VAM-11
- ECG module: ECG-21
- ECG lead
- Footswitch:
 - 971-SWNOM (2-pedal)
 - SP-997-350 (3-pedal)
- Mobile trolley
 - UMT-200
 - Weight: 21kg
 - Width: 470mm
 - Depth: 657mm
 - Height selective (not available after installed)
 - ✓ Platform: 810-870mm
 - ✓ Handle position: 890-950mm
 - UMT-300
 - Without LCD module (with power module and DVD):
 - ✓ Height: 855-1015mm
 - ✓ Width: 514mm
 - ✓ Depth: 653mm
 - ✓ Weight: 43kg
 - With LCD module (with power module and DVD):
 - ✓ Height: 1550-1830mm
 - ✓ Width: 514mm
 - ✓ Depth: 653mm
 - ✓ Weight: 52kg
 - ✓ Platform height (adjustable): 855-1010mm
- Pack
- Dust-proof cover
- Battery Pack (LI23I001A)
- Wireless-LAN adapter
- Probes
- Needle-guided brackets

Application

- Abdomen
- Obstetrics
- Gynecology
- Cardiology
- Small Parts
- Urology
- Vascular
- Pediatrics

Exam Mode

- Adult ABD
- ABD-Difficult
- Ped-ABD
- Neonatal ABD
- Kidney
- OB1
- OB2/3
- Fetal Cardiac
- GYN
- Adult Cardiac
- CAR-Difficult
- Ped-Cardiac
- Neonatal CAR
- Carotid
- IMT
- Lower Ext Artery
- Lower Ext Vein
- Upper Ext Artery
- Upper Ext Vein
- TCI (TCD for FDA version)
- Urology
- Prostate
- Thyroid
- Breast
- Testicle
- MSK
- Superficial
- Orthopedic
- Neonatal Head
- Nerve
- EM ABD
- EM FAST
- EM OB
- EM Vascular
- EM Superficial
- User-defined (1~15)

Imaging Mode

- B-Mode with Tissue Harmonic Imaging
- Slant scanning for linear probes (B, color/power, PW/CW independent)
- M -Mode
- Color M Mode (CM)
- Free Xros M Mode
- Curved Free Xros M Mode (Free Xros CM)
- Color Free Xros M

- Trapezoid Imaging for Linear Probe
- ExFOV Imaging for Convex Probe
- Color(CDFI)
- Power(CDE/PDE)
- D-CDE (D-PDE)
- PW (Pulse Wave Doppler)
- HPRF (High Pulse Repeat Frequency)
- CW (Continuous Wave Doppler)
- TDI (Tissue Doppler imaging)
 - TVI (Tissue Velocity Imaging)
 - TEI (Tissue Energy Imaging)
 - TVM (Tissue Doppler Velocity M Mode)
- Smart 3D
- Static 3D
- 4D (Real-time 3D)
- iScape™
- Tissue Doppler Imaging
- TDI Quantitative Analysis Package
- Contrast Harmonic Imaging
- iBeam™ (Spatial Compounding Imaging for Linear and Convex Probe)
- Multi-frequency probes for 2D and Doppler imaging modes
- iClear™: adaptive speckle suppression imaging for all probes
- iTouch™ (B/PW/CW/Color)
- TSI (Tissue Specific Imaging)
 - Color mode: 7707Hz (Max.)
 - PW mode: 6600Hz (Max.)
 - CW mode: 44000Hz (Max.)
- Adjustable focus number: 4
- System processing channels: 1024
- Magnification factor:
 - Spot: 1-10
 - Pan: 1-10
- Full screen (iZoom): zoom in the image area only, or zoom in both the image area and some other elements
- System dynamic range: ≥160dB
- Adjustable focus positions (Max.): 16
- Maximum frame rate in 4D reaches 30 frames/s
- Frame compare
- Display Mode:
 - B/C/D triplex mode
 - Dual live: B/C, B/TDI,
 - Adjustable 2D/ time line display format
 - Single window
 - Dual-split: B/C, B/TDI, B/M, B/PW
 - Quad-split
- Maximum iScape imaging length: 110cm

Imaging Features

- Display Depth
 - Minimum: 18mm----L14-6s
 - Maximum: 388mm-----C5-2s
- Frame rate (Max.):
 - B mode: 643----L14-6s
 - Color mode: 368----P4-2s
- PRF (probe dependent)
 - Color mode: 14.3kHz
 - PW mode: 24kHz
 - CW mode: 160kHz
- Flow velocities (probe dependent)
 - Color mode: 226cm/s
 - PW mode: 462cm/s
 - CW mode: 3080cm/s
- WF (1-7 levels)

System Language

- Software display and keyboard input available: Chinese/English/German/Spanish/French/Italian/Portuguese/Russian/Czech/Polish
- Keyboard input available only: Icelandic/Norwegian/Swedish/Finnish/Turkish/Danish
- Control panel overlay available: Chinese/German/Spanish/French/Italian/Portuguese/Russian/Czech/Polish
- Operation manual available: Chinese/English/German/Spanish/French/Italian/Portuguese/Russian

System Configuration

Standard Configuration

- High resolution 15 inch LCD display
- PW
- HPRF
- Color doppler flow imaging
- Power doppler flow imaging
- Directional power doppler flow imaging
- Tissue harmonic imaging
- Trapezoid imaging
- iBeam™
- iTouch™
- iStation™
- 320G integrated hard disk
- Multi-language screen display and control panel overlay
- Travelling case

Software Options

- iClear™
- CW module
- iScape module
- Free Xros M (Anatomical M)
- Smart 3D module
- 4D module
- IMT
- TDI(Tissue Doppler imaging) module
- Abdominal package (including related exam mode, comments, measurements, body marks and report)
- Obstetrical package (including related exam mode, comments, measurements, body marks and report)
- Gynecological package (including related exam mode, comments, measurements, body marks and report)
- Cardiac package (including related exam mode, comments, measurements, body marks and report)
- Small parts package (including related exam mode, comments, measurements, body marks and report)
- Urological package (including related exam mode, comments, measurements, body marks and report)
- Vascular package (including related exam mode, comments, measurements, body marks and report)
- Pediatric package (including related exam mode, comments, measurements, body marks and report)
- Nerve blocks package (including related exam mode, comments, measurements, body marks and report)

- Emergency medicine package (including related exam mode, comments, measurements, body marks and report)
- DICOM basic function module (including: task management, DICOM storage, DICOM print, DICOM storage commitment, DICOM media storage (including DICOM DIR), etc.)
- DICOM Worklist
- DICOM MPPS
- DICOM OB/GYN structured report
- DICOM vascular structured report
- DICOM cardiac structured report
- DICOM Query/Retrieve
- Free Xros CM
- TDI Quantitative Analysis

Display Annotations

- Manufacturer logo
- Hospital name: up to 64 characters can be displayed
- Exam date: 3 types selectable, YY/MM/DD, MM/DD/YY, DD/MM/YY
- Exam time: 2 formats
- Acoustic output indices: MI, TIC, TIS, TIB
- Freeze icon
- Gender
- Age
- ID: up to 64 characters can be displayed
- Name: up to 64 characters can be displayed
- Probe model
- Current exam mode
- ECG icon (displays when connects with a physiology module)
- Accession#
- Operator: up to 64 characters can be displayed
- Menu
- Image
- ECG trace
- Probe orientation mark
- Time line
- Coordinate axis, including depth, time, velocity/frequency
- TGC curve
- Focus
- Comment
- Body Mark

- Measure caliper
- Gray/ color scale bar
- Thumbnail
- Cine icon
- Trackball functionality status icon
- Help information
- Soft Menu
- Status icons
- Biopsy guideline
- Measure result window(up to 8 results can be displayed)
- Image parameters

Comments and Body Mark

Comment

Text comment

- Comment text (option)
 - Abdomen: 89
 - OB: 97
 - Cardiology: 80
 - GYN: 69
 - Vascular: 110
 - Urology: 61
 - SMP: 124
 - Pediatrics: 35
 - Nerve blocks: 52
 - EM: 127
- User-defined Comments
 - Add
 - Delete

Arrow

- Arrow Size
- Arrow position
- Arrow orientation

Trace

- Control panel operation

Body Mark

Application package (Option)

- Abdomen: 13
- OB: 25
- Cardiology: 18
- GYN: 7
- Vascular: 17
- Urology: 7
- SMP: 46

- Nerve blocks: 32
- EM: 38

User-defined

- New
- Copy
- Export
- Load
- Delete
- Edit

Storage/ Connection

- 320G integrated hard disk
- External DVD-R/W (Optional)
- USB ports
- Image archive on hard disk and DVD, temporary saving in cine memory
- Live capture: Retrospective (1-120s, or 1-120 cycles); Prospective (1-480s, or 1-120 cycles)
- Thumbnail
- Single image formats: BMP, JPG, DCM, FRM, supports off-line analysis
- Multi-frame images formats: AVI, DCM, CIN, supports off-line analysis
- Clip length: 1-60s, 1-16 cycles
- Storage area:
 - Image area: 640×480
 - Standard area: 800×600
 - Full-screen: 1024×768
- iVision
- Cine review: Auto, Manual (auto review segment can be set), supports linked cine review for 2D, M/D images.
- Send/ print image after End Exam
- Cine memory capacity (Max.)
 - B mode: 8380 frames----L14-6s
 - Color mode: 7413 frames----L14-6s (11457 if BC wide function is turned on)
 - PW/M mode: 131s
- Max. frames in HDD
 - 11184810 frames (JPG format)
 - 138026 frames (FRM format)
- DICOM:
 - DICOM Storage
 - DICOM print
 - DICOM Worklist

- Query/ Retrieve
- Structured Report (SR)
- Storage Commitment
- MPPS
- Media review

iStation™

Intelligent patient data management platform

- Integrated search engine for patient data
- Detailed patient information view
- Intelligent data backup/ restore
- Patient data/ image sending
- Patient data deleting
- Exam managing: create new exam, activate exam and continue exam
- Recycle Bin

Measure/Calc/Study

Caliper

2D-mode

- Depth
- Distance
- Angle
- Area
- Volume
- Cross
- Parallel
- T Length
- Ration (D)
- Ratio (A)
- B-Hist
- B-Profile (not available for M7T)
- Color Vel
- VF Diam

M-mode

- HR
- Slope
- Distance
- Time
- Velocity

Doppler mode

- D Velocity
- HR

- Time
- Acceleration
- D Trace
- PS/ED

Application

Optional package for various specific clinical uses

Abdomen

- 2D-mode Measure
 - Liver
 - Renal L (Renal Length)
 - Renal H (Renal Height)
 - Renal W (Renal Width)
 - Cortex (Renal Cortical Thickness)
 - Adrenal L (Adrenal Length)
 - Adrenal H (Adrenal Height)
 - Adrenal W (Adrenal Width)
 - CBD (Common bile duct)
 - Portal V Diam (Portal Vein Diameter)
 - CHD (Common hepatic duct)
 - GB L (Gallbladder Length)
 - GB H (Gallbladder Height)
 - GB wall th (Gallbladder wall thickness)
 - Panc duct (Pancreatic duct)
 - Panc head (Pancreatic head)
 - Panc body (Pancreatic body)
 - Panc tail (Pancreatic tail)
 - Spleen
 - Aorta Diam (Aorta Diameter)
 - Aorta Bif
 - Iliac Diam
 - Pre-BL L (Previous-Bladder Length)
 - Pre-BL H (Previous-Bladder Height)
 - Pre-BL W (Previous-Bladder Width)
 - Post-BL L (Posterior-Bladder Length)
 - Post-BL H (Posterior-Bladder Height)
 - Post-BL W (Posterior-Bladder Width)
- 2D-mode Calculation
 - Renal Vol (Renal Volume)
 - Pre-BL Vol (Previous-Bladder Volume)
 - Post-BL Vol (Posterior-Bladder Volume)
 - Mictur.Vol (Micturated Volume)
- 2D-mode study
 - Kidney
 - Adrenal

- Bladder
- Doppler-mode Measure
 - Ren A Org (Renal Artery Origin)
 - Arcuate A (Arcuate Artery)
 - Segment A (Segmental Artery)
 - Interlobar A (Interlobar Artery)
 - Renal A (Renal Artery)
 - M Renal A (Main Renal Artery)
 - Renal V (Renal Vein)
 - Aorta
 - Celiac Axis
 - SMA (Superior Mesenteric Artery)
 - C Hepatic A (Common Hepatic Artery)
 - Hepatic A (Hepatic Artery)
 - Splenic A (Splenic Artery)
 - IVC (Inferior Vena Cava)
 - Portal V (Portal Vein)
 - M Portal V (M Portal Vein)
 - Hepatic V (Hepatic Vein)
 - M Hepatic V (Middle Hepatic Vein)
 - Splenic V (Splenic Vein)
 - SMV (Superior Mesenteric Vein)

Obstetrics

- 2D-mode Measure
 - GS (Gestational Sac Diameter)
 - YS (Yolk Sac)
 - CRL (Crown Rump Length)
 - NT (Nuchal Translucency)
 - BPD (Biparietal Diameter)
 - OFD (Occipital Frontal Diameter)
 - HC (Head Circumference)
 - AC (Abdominal Circumference)
 - FL (Femur Length)
 - TAD (Abdominal Transversal Diameter)
 - APAD (Anteroposterior Abdominal Diameter)
 - TCD (Cerebellum Diameter)
 - Cist Magna (Cist Magna)
 - LVW (Lateral Ventricle Width)
 - HW (Hemisphere Width)
 - OOD (Outer Orbital Diameter)
 - IOD (Inter Orbital Diameter)
 - HUM (Humerus Length)
 - Ulna (Ulna Length)
 - RAD (Radius Length)
 - Tibia (Tibia Length)

- FIB (Fibula Length)
- CLAV (Clavicle Length)
- Vertebrae (Length of Vertebrae)
- MP (Middle Phalanx Length)
- Foot (Foot Length)
- Ear (Ear Length)
- APTD (Anteroposterior trunk diameter)
- TTD (Transverse trunk diameter)
- FTA (Fetal Trunk Cross-sectional Area)
- THD (Thoracic Diameter)
- HrtC (Heart Circumference)
- TC (Thoracic circumference)
- Umb VD (Umbilical Vein Diameter)
- F-kidney (Fetal kidney Length)
- Mat Kidney (Matrix Kidney Length)
- Cervix L (Cervical Length)
- AF (Amniotic Fluid)
- NF (Nuchal Fold)
- Orbit (Orbit)
- PL Thickness (Placental Thickness)
- Sac Diam1 (Gestational Sac Diameter 1)
- Sac Diam2 (Gestational Sac Diameter 2)
- Sac Diam3 (Gestational Sac Diameter 3)
- AF1 (Amniotic Fluid 1)
- AF2 (Amniotic Fluid 2)
- AF3 (Amniotic Fluid 3)
- AF4 (Amniotic Fluid 4)
- LVIDd (Left Ventricular Internal Diameter at End-diastole)
- LVIDs (Left Ventricular Internal Diameter at End-systole)
- LV Diam (Left Ventricular Diameter)
- LA Diam (Left Atrium Diameter)
- RVIDd (Right Ventricular Internal Diameter at End-diastole)
- RVIDs (Right Ventricular Internal Diameter at End-systole)
- RV Diam (Right Ventricular Diameter)
- RA Diam (Right Atrium Diameter)
- IVSd (Interventricular Septal Thickness at End-diastole)
- IVSs (Interventricular Septal Thickness at End-systole)
- IVS (Interventricular Septal Thickness)
- LV Area (Left Ventricular Area)
- LA Area (Left Atrium Area)

- RV Area (Right Ventricular Area)
 - RA Area (Right Atrium Area)
 - Ao Diam (Aorta Diameter)
 - MPA Diam (Main Pulmonary Artery Diameter)
 - LVOT Diam (Left Ventricular Outflow Tract Diameter)
 - RVOT Diam (Right Ventricular Outflow Tract Diameter)
 - 2D-mode Calculation
 - Mean Sac Diam (Mean Gestational Sac Diameter)
 - AFI
 - EFW1 (Estimated Fetal Weight 1)
 - EFW2 (Estimated Fetal Weight 2)
 - HC/AC
 - FL/AC
 - FL/BPD
 - AXT
 - CI
 - FL/HC
 - HC(c)
 - HrtC/TC
 - TCD/AC
 - LVW/HW
 - LVD/RVD
 - LAD/RAD
 - AoD/MPAD
 - LAD/AoD
 - 2D-mode Study
 - AFI (Auto)
 - M-mode Measure
 - FHR (Fetal Heart Rate)
 - LVIDd (Left ventricular diameter at end diastole)
 - LVIDs (Left ventricular diameter at end systole)
 - RVIDd (Right ventricular diameter at end diastole)
 - RVIDs (Right ventricular diameter at end systole)
 - IVSd (interventricular septal thickness at end diastole)
 - IVSs (interventricular septal thickness at end systole)
 - Doppler-mode Measure
 - Umb A (Umbilical Artery)
 - Duct Venos (Ductus Venos)
 - Placenta A (Placenta Artery)
 - MCA (Middle Cerebral Artery)
 - Fetal Ao (Fetal Aorta)
 - Desc Aorta (Descending Aorta)
 - Ut A (Uterine Artery)
 - Ovarian A (Ovarian Artery)
 - FHR (Fetal Heart Rate)
- Available Obstetrics Formulae**
- GA (gestational age) Formulae
 - GS: 4
 - CRL: 9
 - BPD: 11
 - HC: 6
 - AC: 3
 - FL: 12
 - OFD: 3
 - FTA: 1
 - THD: 1
 - HUM: 2
 - CLAV: 1
 - TCD: 2
 - OOD: 1
 - EFW1: 2
 - EFW2: 2
 - Mean Sac Diam: 1
 - FG (fetal growth) Formulae
 - GS: 4
 - CRL: 6
 - BPD: 11
 - HC: 6
 - AC: 6
 - FL: 10
 - OFD: 4
 - APAD: 1
 - TAD: 1
 - FTA: 1
 - THD: 1
 - HUM: 2
 - Ulna: 1
 - Tibia: 1
 - RAD: 2
 - FIB: 2
 - CLAV: 1
 - TCD: 3
 - Cist Magna: 1
 - EFW1: 9
 - EFW2: 9

- MCA PI: 1
- MCA RI: 1
- Umb A PI: 1
- Umb A RI: 1
- AFI: 1
- Fetal Weight Formulae: 11

Cardiology

- 2D-mode Measure
 - LA Diam (Left Atrium Diameter)
 - LA Major (Left Atrium major Diameter)
 - LA Minor (Left Atrium minor Diameter)
 - RA Major (Right Atrium major Diameter)
 - RA Minor (Right Atrium minor Diameter)
 - LV Major (Left Ventricular major Diameter)
 - LV Minor (Left Ventricular minor Diameter)
 - RV Major (Right Ventricular major Diameter)
 - RV Minor (Right Ventricular minor Diameter)
 - LA Area (Left Atrium area)
 - RA Area (Right Atrium area)
 - LV Area (d) (Left Ventricular area at end-diastole)
 - LV Area (s) (Left Ventricular area at end-systole)
 - RV Area (d) (Right Ventricular area at end-diastole)
 - RV Area (s) (Right Ventricular area at end-systole)
 - LVIDd (Left Ventricular Internal Diameter at end-diastole)
 - LVIDs (Left Ventricular Internal Diameter at end-systole)
 - RVDd (Right Ventricular Diameter at end-diastole)
 - RVDs (Right Ventricular Diameter at end-systole)
 - LVPWd (Left Ventricular Posterior wall thickness at end-diastole)
 - LVPWs (Left Ventricular Posterior wall thickness at end-systole)
 - RVAWd (Right Ventricular Anterior wall thickness at end-diastole)
 - RVAWs (Right Ventricular Anterior wall thickness at end-systole)
 - IVSd (Interventricular Septal thickness at end-diastole)
 - IVSs (Interventricular Septal thickness at end-systole)
 - Ao Diam (Aorta Diameter)
 - Ao Arch Diam (Aorta arch Diameter)
 - Ao Asc Diam (Ascending Aorta Diameter)
 - Ao Desc Diam (Descending Aorta Diameter)
 - Ao Isthmus (Aorta Isthmus Diameter)
 - Ao st junct (Aorta ST junct Diameter)
 - Ao Sinus Diam (Aorta Sinus Diameter)
 - Duct Art Diam (Ductus Arteriosus Diameter)
 - Pre Ductal (Previous ductal Diameter)
 - Post Ductal (Posterior ductal Diameter)
 - ACS (Aortic Valve Cusp Separation)
 - LVOT Diam (Left Ventricular Outflow Tract Diameter)
 - AV Diam (Aorta Valve Diameter)
 - AVA (Aortic Valve Area)
 - PV Diam (Pulmonary valve Diameter)
 - LPA Diam (Left pulmonary Artery Diameter)
 - RPA Diam (Right pulmonary Artery Diameter)
 - MPA Diam (Main pulmonary Artery Diameter)
 - RVOT Diam (Right Ventricular Outflow Tract Diameter)
 - MV Diam (Mitral Valve Diameter)
 - MVA (Mitral Valve area)
 - MCS (Mitral Valve Cusp Separation)
 - EPSS (Distance between point E and Interventricular Septum when mitral valve is fully open)
 - TV Diam (Tricuspid valve Diameter)
 - TVA (Tricuspid Valve Area)
 - IVC Diam (Insp) (Inferior vena cava inspiration Diameter)
 - IVC Diam (Expir) (Inferior vena cava expiration Diameter)
 - SVC Diam (Insp) (Superior vena cava inspiration Diameter)
 - SVC Diam (Expir) (Superior vena cava expiration Diameter)
 - LCA (Left Coronary Artery)
 - RCA (Right Coronary Artery)
 - VSD Diam (Ventricular Septal defect Diameter)
 - ASD Diam (Atrial Septal defect Diameter)
 - PDA Diam (Patent ductus Arteriosus Diameter)
 - PFO Diam (Patent Oval Foramen Diameter)
 - PEd (Pericardial Effusion at diastole)
 - PEs (Pericardial Effusion at systole)
- 2D-mode Calculation

- LA/Ao (LA Diam (cm) / Ao Diam (cm))
- Ao/LA (Aorta Diameter/Left Atrium Diameter)
- M-mode Measure
 - LA Diam (Left Atrium Diameter)
 - LVIDd (Left Ventricular Internal Diameter at end-diastole)
 - LVIDs (Left Ventricular Internal Diameter at end-systole)
 - RVDd (Right Ventricular Diameter at end-diastole)
 - RVDs (Right Ventricular Diameter at end-systole)
 - LVPWd (Left Ventricular Posterior wall thickness at end-diastole)
 - LVPWs (Left Ventricular Posterior wall thickness at end-systole)
 - RVAWd (Right Ventricular Anterior wall thickness at end-diastole)
 - RVAWs (Right Ventricular Anterior wall thickness at end-systole)
 - IVSd (Interventricular Septal thickness at end-diastole)
 - IVSs (Interventricular Septal thickness at end-systole)
 - Ao Diam (Aorta Diameter)
 - Ao Arch Diam (Aorta arch Diameter)
 - Ao Asc Diam (Ascending Aorta Diameter)
 - Ao Desc Diam (Descending Aorta Diameter)
 - Ao Isthmus (Aorta Isthmus Diameter)
 - Ao st junct (Aorta ST junct Diameter)
 - Ao Sinus Diam (Aorta Sinus Diameter)
 - LVOT Diam (Left Ventricular outflow tract Diameter)
 - ACS (Aortic valve Cusp Separation)
 - LPA Diam (Left pulmonary Artery Diameter)
 - RPA Diam (Right pulmonary Artery Diameter)
 - MPA Diam (Main pulmonary Artery Diameter)
 - RVOT Diam (Right Ventricular outflow tract Diameter)
 - MV E Amp (Amplitude of the Mitral Valve E wave)
 - MV A Amp (Amplitude of the Mitral Valve A wave)
 - MV E-F Slope (Mitral Valve E-F slope)
 - MV D-E Slope (Mitral Valve D-E slope)
 - MV DE (Amplitude of the Mitral Valve DE wave)
 - MCS (Mitral Valve Cusp Separation)
 - EPSS (Distance between point E and the interventricular septum)
- PEd (Pericardial effusion at diastole)
- PEs (Pericardial effusion at systole)
- LVPEP (Left Ventricular pre-ejection period)
- LVET (Left Ventricular ejection time)
- RVPEP (Right Ventricular pre-ejection period)
- RVET (Right Ventricular ejection time)
- HR (Heart Rate)
- M-mode Calculation
 - LA/Ao
 - Ao/LA (Aorta Diameter/Left Atrium Diameter)
- Doppler Measure
 - MV Vmax (Mitral Valve Maximum Velocity)
 - MV E Vel (Mitral Valve E-wave Velocity)
 - MV A Vel (Mitral Valve A-wave Velocity)
 - MV E VTI (Mitral Valve E-wave Velocity)-Time Integral
 - MV A VTI (Mitral Valve A-wave Velocity)-Time Integral
 - MV VTI (Mitral Valve Velocity)-Time Integral
 - MV AccT (Mitral Valve Acceleration Time)
 - MV DecT (Mitral Valve Deceleration Time)
 - IVRT (isoVelocity Relaxation Time)
 - IVCT (isoVelocity Compression Time)
 - MV E Dur (Mitral Valve E-wave Duration)
 - MV A Dur (Mitral Valve A-wave Duration)
 - LVOT Vmax (Left Ventricular Outflow Tract Velocity)
 - LVOT VTI (Left Ventricular Outflow Tract Velocity)-Time Integral
 - LVOT AccT (Left Ventricular Outflow Tract Acceleration Time)
 - AAO Vmax (Ascending Aorta Maximum Velocity)
 - DAo Vmax (Descending Aorta Maximum Velocity)
 - AV Vmax (Aorta Valve Maximum Velocity)
 - AV VTI (Aorta Valve Velocity)-Time Integral
 - LVPEP (Left Ventricular Pre-ejection Period)
 - LVET (Left Ventricular Ejection Time)
 - AV AccT (Aorta Valve Acceleration Time)
 - AV DecT (Aorta Valve Deceleration Time)
 - RVET (Right Ventricular Ejection Time)
 - RVPEP (Right Ventricular Pre-ejection Period)
 - TV Vmax (Tricuspid Valve Maximum Velocity)
 - TV E Vel (Tricuspid Valve E-wave Flow Velocity)
 - TV A Vel (Tricuspid Valve A-wave Flow Velocity)

- TV VTI (Tricuspid Valve Velocity)-Time Integral)
- TV AccT (Tricuspid Valve Acceleration Time)
- TV DecT (Tricuspid Valve Deceleration Time)
- TV A Dur (Tricuspid Valve A-wave Duration)
- RVOT Vmax (Right Ventricular Outflow Tract Maximum Velocity)
- RVOT VTI (Right Ventricular Outflow Tract Velocity)-Time Integral)
- PV Vmax (Pulmonary Valve Maximum Velocity)
- PV VTI (Pulmonary Valve Velocity)-Time Integral)
- PV AccT (Pulmonary Valve Acceleration Time)
- MPA Vmax (Main Pulmonary Artery Maximum Velocity)
- RPA Vmax (Right Pulmonary Artery Maximum Velocity)
- LPA Vmax (Left Pulmonary Artery Maximum Velocity)
- PVein S Vel (Pulmonary Vein S-wave Flow Velocity)
- PVein D Vel (Pulmonary Vein D-wave Flow Velocity)
- PVein A Vel (Pulmonary Vein A-wave Flow Velocity)
- PVein A Dur (Pulmonary Vein A-wave Duration)
- PVein S VTI (Pulmonary Vein S-wave Velocity)-time Integral)
- PVein D VTI (Pulmonary Vein D-wave Velocity)-time Integral)
- PVein DecT (Pulmonary Vein Deceleration Time)
- IVC Vel (Insp) (Inferior Vena Cava Inspiration Maximum Velocity)
- IVC Vel (Expir) (Inferior Vena Cava Expiration Maximum Velocity)
- SVC Vel (Insp) (Superior Vena Cava Inspiration Maximum Velocity)
- SVC Vel (Expir) (Superior Vena Cava Expiration Maximum Velocity)
- MR Vmax (Mitral Valve Regurgitation Maximum Velocity)
- MR VTI (Mitral Valve Regurgitation Velocity)-Time Integral)
- MS Vmax (Mitral Valve Stenosis Maximum Velocity)
- dP/dt (Rate of Pressure Change)
- AR Vmax (Aortic Valve Regurgitation Maximum Velocity)
- AR VTI (Aortic Valve Regurgitation Velocity)-Time Integral)
- AR DecT (Aortic Valve Regurgitation Deceleration Time)
- AR PHT (Aortic Valve Regurgitation Pressure Half Time)
- AR Ved (Aortic Valve Regurgitation Velocity) at end-Diastole)
- TR Vmax (Tricuspid Valve Regurgitation Maximum Velocity)
- TR VTI (Tricuspid Valve Regurgitation Velocity)-Time Integral)
- PR Vmax (Pulmonary Valve Regurgitation Maximum Velocity)
- PR VTI (Pulmonary Valve Regurgitation Velocity)-Time Integral)
- PR PHT (Pulmonary Valve Regurgitation Pressure Half Time)
- PR Ved (Pulmonary Valve Regurgitation Velocity) at end-Diastole)
- VSD Vmax (Ventricular Septal Defect Maximum Velocity)
- ASD Vmax (Atrial Septal Defect Maximum Velocity)
- PDA Vel (d) (Patent Ductus Arteriosus Velocity at End-diastole)
- PDA Vel (s) (Patent Ductus Arteriosus Velocity at End-systole)
- Coarc Pre-Duct (Coarctation of Pre-Ductus)
- Coarc Post-Duct (Coarctation of Post-Ductus)
- HR (Heart Rate)
- RAP (Right Atrium Pressure)
- Doppler-mode Calculation
 - MV E/A (MV E Vel (cm/s) / MV A Vel (cm/s))
 - MVA(PHT) (MVA(PHT) (cm²) = 220 / MV PHT (ms)Mitral Valve Orifice Area (PHT))
 - TV E/A (Tricuspid Valve E-Vel/A-Vel)
 - TVA(PHT) (Tricuspid Valve Orifice Area (PHT))
- TDI Measure
 - Ea(medial) (Mitral Valve medial Early diastolic motion)
 - Aa(medial) (Mitral Valve medial Late diastolic motion)
 - Sa(medial) (Mitral Valve medial Systolic motion)
 - ARa(medial) (Mitral Valve medial Acceleration

- Rate)
 - DRa(medial) (Mitral Valve medial Deceleration Rate)
 - Ea(lateral) (Mitral Valve lateral Early diastolic motion)
 - Aa(lateral) (Mitral Valve lateral Late diastolic motion)
 - Sa(lateral) (Mitral Valve lateral Systolic motion)
 - ARa(lateral) (Mitral Valve lateral Acceleration Rate)
 - DRa(lateral) (Mitral Valve lateral Deceleration Rate)

- Cardiac Study Items

- 2D-mode:

- S-P Ellipse
- B-P Ellipse
- Bullet
- Mod.Simpson
- Simpson SP (A2C)
- Simpson SP (A4C)
- Simpson BP
- Cube
- Teichholz
- Gibson
- LA Vol(A-L)
- LA Vol (Simp)
- RA Vol (Simp)
- LV Mass (Cube)
- LV Mass (A-L)
- LV Mass (T-E)
- Qp/Qs
- PISA MR
- PISA AR
- PISA TR
- PISA PR

- M-mode:

- LVIMP
- Cube
- Teichholz
- Gibson
- LV Mass (Cube)

- Doppler-mode:

- MVA(VTI)
- AVA(VTI)
- LV TEI

- RVSP
- PAEDP
- RV TEI
- Qp/Qs
- PISA MR
- PISA AR
- PISA TR
- PISA PR
- TDI mode
 - Ea/Aa (medial)
 - ATa (medial)
 - DTa (medial)

- **Vascular**

- 2D-mode Measure

- Vas Diam (Vascular Diameter)
- Vas Area (Vascular Area)
- Normal (D) (Vessel Diameter)
- Resid (D) (Residual Diameter)
- Normal (A) (Vessel Area)
- Resid (A) (Residual Area)
- CCA IMT (Common Carotid Artery IMT)
- Bulb IMT (Bulbillate IMT)
- ICA IMT (Internal Carotid Artery IMT)
- ECA IMT (External Carotid Artery IMT)

- 2D-mode Calculation

- Stenosis D (Stenosis Diameter)
- Stenosis A (Stenosis Area)
- Vol Flow(Diam)- TAMAX (Volume Flow Diameter)
- Vol Flow(Area)- TAMAX (Volume Flow Area)

- 2D-mode Study

- Volume Flow
- Stenosis
- IMT (Intima-Media Thickness)

- Doppler-mode Measure

- CCA (Common Carotid Artery)
- Bulb (Bulbillate)
- ICA (Internal Carotid Artery)
- ECA (External Carotid Artery)
- Vert A (Vertebral Artery)
- Innom A (Innominate Artery)
- Subclav A (Subclavian Artery)
- Axill A (Axillary Artery)
- Brachial A (Brachial Artery)
- Ulnar A (Ulnar Artery)
- Radial A (Radial Artery)

- Subclav A (Subclavian Artery)
- Axill V (Axillary Vein)
- Cephalic V (Cephalic Vein)
- Basilic V (Basilic Vein)
- Ulnar V (Ulnar Vein)
- Radial V (Radial Vein)
- C.Iliac A (Common Iliac Artery)
- Ex.Iliac A (External Iliac Artery)
- CFA (Common Femoral Artery)
- SFA (Superficial Femoral Artery)
- Pop A (Popliteal Artery)
- TP Trunk A (Tibial Peroneal Trunk Artery)
- Peroneal A (Peroneal Artery)
- P.Tib A (Posterior Tibial Artery)
- A.Tib A (Anterior Tibial Artery)
- Dors.Ped A (Dorsalis Pedis Artery)
- C.Iliac V (Common Iliac Vein)
- Ex.Iliac V (External Iliac Vein)
- Femoral V (Femoral Vein)
- Saph V (Great Saphenous Vein)
- Pop V (Popliteal Vein)
- TP Trunk V (Tibial Peroneal Trunk Vein)
- Sural V (Sural Vein)
- Soleal V (Soleal Vein)
- Peroneal V (Peroneal Vein)
- P.Tib V (Posterior Tibial Vein)
- A.Tib V (Anterior Tibial Vein)
- ACA (Anterior Cerebral Artery)
- MCA (Middle Cerebral Artery)
- PCA (Posterior Cerebral Artery)
- AComA (Ant.communicating br.)
- PComA (Post.communicating br.)
- BA (Basilar Artery)
- IIA (Internal Iliac Artery)
- PFA (Deep Femoral Artery)
- Ba V (Basilar Vein)
- Brachial V (Brachial Vein)
- IIV (Internal Iliac Vein)
- CFV (Common Femoral Vein)
- SFV (Superficial Femoral Vein)
- PFV (Deep Femoral Vein)
- SSV (Small Saphenous Vein)
- Vas Trace (Vascular Trace)
- Doppler-mode Study
 - Volume Flow

Gynecology

- 2D-mode Measure
 - UT L
 - UT H
 - UT W
 - Cervix L
 - Cervix H
 - Cervix W
 - Endo
 - Ovary L
 - Ovary H
 - Ovary W
 - Follicle1-16 L
 - Follicle1-16 W
 - Follicle1-16 H
- 2D-mode Calculation
 - Ovary Vol
 - UT Vol
 - Uterus Body
 - UT-L/ CX-L
- 2D-mode Study
 - Uterus (Length, height and width of uterus, endometrium thickness)
 - Uterine Cervix (Length, height and width of uterine cervix)
 - Ovary (Length, height and width of ovary)
 - Follicle 1-16 (Length and width of follicle 1-16)

Urology

- 2D-mode Measure
 - Renal L
 - Renal H
 - Renal W
 - Cortex
 - Adrenal L
 - Adrenal H
 - Adrenal W
 - Prostate L
 - Prostate H
 - Prostate W
 - Seminal L
 - Seminal H
 - Seminal W
 - Testis L
 - Testis H
 - Testis W

- Pre-BL L
- Pre-BL H
- Pre-BL W
- Post-BL L
- Post-BL H
- Post-BL W
- 2D-mode Calculation
 - Renal Vol
 - Prostate Vol
 - Testis Vol
 - Pre-BL Vol
 - Post-BL Vol
 - Mictur.Vol
- 2D-mode Study
 - Kidney
 - Adrenal
 - Prostate
 - Seminal Vesicle
 - Testis
 - Bladder

Small Parts

- 2D-mode Measure
 - Thyroid L
 - Thyroid H
 - Thyroid W
 - Isthmus H
 - Testis L (Testicular Length)
 - Testis H (Testicular Height)
 - Testis W (Testicular Width)
 - Mass1 D1-3
 - Mass2 D1-3
 - Mass3 D1-3
- 2D-mode Calculation
 - Thyroid Vol
- 2D-mode Study
 - Thyroid
 - Testic
 - Mass1-3
- Doppler-mode Measure
 - STA

- ITA

Orthopedics

- 2D-mode Measure
 - HIP
 - HIP-Graf

Diagnostic Report

- View/add images
- Edit report
- Obstetric/vascular analysis
- Fetal growth curve
- Print report
- Import/export report
- View history report

Safety & Conformance

Quality Standards

- ISO 9001:2000
- ISO 13485:2003

Design Standards

- UL 60601-1
- CSA C22.2 No. 601-1
- EN 60601-1 and IEC 60601-1
- EN 60601-1-1 and IEC 60601-1-1
- EN 60601-1-2 and IEC 60601-1-2
- EN 60601-2-37 and IEC60601-2-37
- EN60601-1-4 and IEC60601-1-4
- EN60601-1-6 and IEC60601-1-6

CE Declaration

M7/ M7T system is fully in conformance with the Council Directive 93/42/EEC Concerning Medical Devices, as amended by 2007/47/EC. The number adjacent to the CE marking (0123) is the number of the EU-notified body that certified meeting the requirements of Annex II of the Directive.

Not all features or specifications described in this document may be available in all probes and/or modes.

No part of this manual may be copied or printed, in whole or in part, without written permission.

The contents of this manual are subject to change without prior notice and without our legal obligation.

Note: the contents in this datasheet are applied to Version 2.0 of system software for M7/M7T diagnostic ultrasound system.